


**IFT**  
Female Tee



**Female NPT Threads**

| Part Number      | Pipe Size | Dimension |      |      |      | Pressure Ratings, psig(bar) |           |
|------------------|-----------|-----------|------|------|------|-----------------------------|-----------|
|                  |           | A         | E    | L    | H    | SS316, Steel                | Brass     |
| <b>IFT - 2N</b>  | 1/8       | 48.0      | 8.6  | 24.0 | 12.7 | 6200(427)                   | 3100(213) |
| <b>IFT - 4N</b>  | 1/4       | 58.0      | 11.4 | 29.0 | 17.5 | 7200(496)                   | 3600(248) |
| <b>IFT - 6N</b>  | 3/8       | 69.0      | 15.0 | 34.5 | 20.6 | 5600(385)                   | 2800(192) |
| <b>IFT - 8N</b>  | 1/2       | 74.0      | 18.5 | 37.0 | 25.4 |                             |           |
| <b>IFT - 12N</b> | 3/4       | 93.0      | 23.9 | 46.5 | 31.8 | 5100(351)                   | 2500(172) |
| <b>IFT - 16N</b> | 1         | 97.0      | 29.7 | 48.5 | 42.9 | 6400(440)                   | 3200(220) |

※ ISO Tapered Threads are available upon request.

• All dimensions in millimeters unless specified as "inch". Dimension are for reference only, subject to change.