


## IRHB

### Reducing Hex Bushing



### Male to Female NPT Threads

Part Number	Male Pipe Size	Female Pipe Size	Dimension			Pressure Ratings, psig(bar)	
			A	E	H	SS316, Steel	Brass
IRHB - 4N - 2N	1/4	1/8	26.9	7.1	14.2	6500(447)	3300(227)
IRHB - 6N - 2N	3/8	1/8	21.8	8.6	17.4	9200(633)	4700(323)
IRHB - 6N - 4N	3/8	1/4	30.2	9.6	19.1	6600(454)	3300(227)
IRHB - 8N - 2N	1/2	1/8	27.4	8.6	22.2	12200(840)	6200(427)
IRHB - 8N - 4N	1/2	1/4	27.4	11.4	22.2	8300(571)	4400(303)
IRHB - 8N - 6N	1/2	3/8	35.8	11.9	22.2	5300(365)	2600(179)
IRHB-12N - 4N	3/4	1/4	27.4	11.4	26.9	12000(826)	6000(413)
IRHB-12N - 6N	3/4	3/8	27.4	15.0	26.9	8200(564)	4300(296)
IRHB-12N - 8N	3/4	1/2	41.4	15.7	26.9	4900(337)	2400(165)
IRHB-16N - 4N	1	1/4	34.8	11.4	34.9	14500(999)	7400(509)
IRHB-16N - 6N	1	3/8	34.8	15.0	34.9	11600(799)	5900(406)
IRHB-16N - 8N	1	1/2	34.8	18.5	34.9	8600(592)	4300(296)
IRHB-16N -12N	1	3/4	47.0	22.4	34.9	5300(365)	2600(179)

※ ISO Tapered Threads are available upon request.